

SAFETY

When It Matters Most



REMZBAUER premium neoprene dry box gloves features high-tensile strength and flexibility for work requiring good sensitivity. These gloves offer a high level of protection from chemicals such as oils, greases, fuels and acetone. Our gloves also offer good permeation resistance against vapours and gases.

Ambidextrous, flexible and comfortable for long use. The 32" glove provides better forearm protection with smooth finish grip, unlined and chlorinated for easy donning or removal. Cuff diameters match 6" and 8" diameter dry box or glove box ports.

These gloves are used where containment of a hazard is needed or the product is of a critical nature where zero contamination is essential. Applications include nuclear and pharmaceutical industries; it is also suitable for sandblasting and cleanroom usage.

Application: • Pharmaceutical • Nuclear Industries • Sandblasting

Product Code	Size	Palm width, mm (± 5mm)	Length, mm (inch)	Glove Port size
HC15KU8-CX-N32 HC30KU8-CX-N32	9	125	760 – 813 mm (30 – 32 inch)	6 inch & 8 inch
Thickness, mils (mm)			13 – 19 mils (0.33 – 0.46 mm) 28 – 36 mils (0.71 – 0.94 mm)	



Poly-chloroprene Long Black Gloves

Product Code	Sizes	Palm width, mm (± 5mm)	Length, mm (inch)	Glove Port size
HC15KUB-CX-N32 HC30KUB-CX-N32	9	125	760 – 813 mm (30 – 32 inch)	6 inch
Thickness, mils (mm)			13 – 18 mils (0.33 – 0.46 mm) 28 – 36 mils (0.71 – 0.84 mm)	

Description:

- Manufactured with poly-chloroprene rubber
- Ambidextrous
- Can be delivered decontaminated or decontaminated - sterile
- Smooth finish & chlorinated.

Compliance:

- Manufactured in accordance with ISO 9001:2015 (reg. AR-1196) & ISO 14001:2015 (reg. ER-0856)
- In compliance with the standards EN 420 – General requirements

Physical Performance

- EN 374 - Protective Gloves against Chemicals & Micro-organisms: Methanol, Acetonitrile & Sulphuric Acid 96%
- ASTM D4679-02(2015)^{e1} on physical testing - minimum physical requirements:

Module 100%	Tensile strength	Ultimate Elongation
< 2 MPa	Min. 15 MPa	Min.500%

Benefits:

- Ideal for use where heavy duty protection is essential.
- Beaded cuff prevents droplets flowing beyond the glove
- Added length for better protection of the forearms

Applications:

This glove is ideal for use where heavy duty chemical protection is essential as well as sandblasting, sanitation, pharmaceutical and in the nuclear industries.

Not recommended for:

Gloves will deteriorate after prolonged contact with solvents (e.g. kerosene, benzene, corn oil, and toluene)

Special Storage Condition:

Avoid contact with direct sunlight
Store at 15°C to 40°C.

Cleaning:

Wash with soapy water, rinse with clean water & low temperature dry (< 40°C)

(ALL INFORMATION ARE SUBJECT TO CHANGE FOR PRODUCT IMPROVEMENTS)

EFFECTIVE DATE: 15.04.2019

QA-S33

REVISION: A



G.B. Industries Sdn Bhd
sales@gb-intl.com